

Part No: RAXXA10-S-18


SMA Attenuators • Male to Female • DC – 18 GHz - 10 W

电气特性 ELECTRICAL

- **Frequency Range** DC – 18 GHz
- **Attenuation (dB)**
 - 1 through 9 ± 0.8 dB
 - 10± 1.0 dB
 - 20 ± 1.0 dB
 - 30 ± 1.0 dB
 - 40 ± 1.0 dB
- **VSWR (MAX)**
 - DC – 4 GHz..... 1.15 : 1
 - 4 – 8 GHz.....1.20 : 1
 - 8 – 12.4 GHz.....1.25 : 1
 - 12.4 – 18 GHz.....1.30 : 1
- **Impedance** 50 Ohms
- **RF Power Nominal** 10 Watts Average at 25°C
 PEAK: 1000 Watts
 (5 μSec Pulse Width , 0.5% Duty Cycle)

机械特性 MECHANICAL

- **Temperature Range** -55°C - +125°C
- **Connectors** Brass ,Nickel Plated
- **Connector Pins** Beryllium Copper, Gold Plated
- **Body** Black, Finned Aluminum
- **Insulators** PTFE, Virgin Electrical Grade



Unit : mm

订货信息 ORDER

Model Number: RAXXA10-S-18
 └──────────┬──────────┘
 dB Value

