

Part No: RAXXA100-N-12.4


N Attenuators • Male to Female • DC – 12.4 GHz - 100 W

电气特性 ELECTRICAL

- **Frequency Range** DC – 12.4 GHz
- **Attenuation (dB)**
 - 3-1.0/+1.5 dB
 - 6-1.0/+3.0 dB
 - 10-1.0/+2.0 dB
 - 20-1.0/+2.0 dB
 - 30-0.7/+1.0 dB
 - 40-0.5/+1.0 dB
 - 50-0.5/+1.5 dB
- **VSWR (MAX)** DC – 12.4 GHz..... 1.30 : 1
- **Impedance** 50 Ohms
- **RF Power Nominal** 100 Watts Average at 25°C
 PEAK: 1000 Watts
 (5 μSec Pulse Width , 10% Duty Cycle)

机械特性 MECHANICAL

- **Temperature Range** -55°C - +125°C
- **Connectors** Brass ,Nickel Plated
- **Connector Pins** Beryllium Copper, Gold Plated
- **Body** Black, Finned Aluminum
- **Insulators** PTFE, Virgin Electrical Grade



Unit:mm

订货信息 ORDER

Model Number : RAXXA100-N-12.4
 └──────────┬──────────┘
 dB Value