

Model: TMLA-060090-1540-12
Low Noise Amplifier
60-90 GHz, NF:3.5 dB, Gain:15 dB
Feature:

- Ultra Wide Band: 60-90 GHz
- Gain: 15dB Min
- Noise Figure: 4.0dB Max
- Unconditional stability

电气特性 Electrical:

参数Parameter	Min.	Typ.	Max.	单位Units
频率范围 Frequency range	60		90	GHz
增益 Gain	15			dB
噪声系数 Noise Figure		3.5		dB
输出功率1dB压缩点 Output P1dB	8			dBm
输入驻波 Input VSWR			2.5	:1
输出驻波 Output VSWR			2.5	:1
直流电压 DC Voltage		+12		V DC
直流供电 DC power supply		150		mA

机械特性 Mechanical :

参数Parameter	指标 Value
输入接口 Input Connector	WR-12/ UG-387/U
输出接口 Output Connecto	WR-12/ UG-387/U
供电引脚 Power Supply Pin	Solder Pin
尺寸 Size	30mm×30mm×23mm







绝对最大值 Absolute Maximum Ratings:

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+12V
输入功率 RF INPUT POWER	10 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V


 Available 220V System
 Benchtop Amplifier

外形尺寸 Outline Drawing:

Unit: mm(Inches)



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES

温度环境 Environmental Conditions:

参数Parameter	Min.	Typ.	Max.	单位Units
操作温度 Operating Temperature	0		+60	°C
存储温度 Non-operating Temperature	-45		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号Revision
TMLA-060090-1540-12	E-band Low Noise Amplifier 60-90 GHz, NF:3.5 dB, Gain:30 dB,WR-12	Rev.1.1