

Model:TLPA18G40G-45-40-HS
Power Amplifier
18-40GHz,Gain:45dB,Psat:40dBm
Feature:

- Ultra Wide Band: 18-40GHz
- Gain:45dB Typ
- Psat Output Power:40dBm Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

电气特性 Electrical Specifications:

参数Parameter	Min	Typ	Max	单位Units
频率范围 Frequency range	18-40			GHz
增益 Gain	40	45		dB
增益平坦度 Gain Flatness		±4	±5	dB
饱和输出功率 Output Psat	37	40		dBm
杂散 Spurious		-60		dBc
输入驻波 Input VSWR		2		:1
直流电压 DC Voltage		+18		V DC
直流电流 DC Supply Current		5		A
阻抗 Impedance	50			Ohms

机械特性 Mechanical Specifications:

参数Parameter	指标 Value	单位Units
输入输出接口 Input /Output Connector	2.92 Female/2.92 Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	132*165*49.5	mm
重量 Weight	/	g


绝对最大值 Absolute Maximum Ratings:

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+20V
输入功率 RF Input Power	0dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V


**Available 220V System
Benchtop Amplifier**

外形尺寸 Outline Drawing:

Unit: mm



温度环境 Environmental Conditions:




参数Parameter	Min	Typ	Max	单位Units
操作温度 Operating Temperature	-40		+50	°C
存储温度 Non-operating Temperature	-45		+65	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:


标准型号 Part Number	描述 Description	版本号Revision
TLPA18G40G-45-40	Power amplifier 18-40GHz,Gain:45dB,Psat:40dBm,+18V DC,Without Heatsink.	Rev.1.1
TLPA18G40G-45-40-HS	Power amplifier 18-40GHz,Gain:45dB,Psat:40dBm,+18V DC,With Heatsink.	Rev.1.1

典型曲线 Typical Performance Data:


P1dB vs Frequency



Psat vs Frequency




Gain vs Frequency



典型曲线 Typical Performance Data:

Harmonic vs Frequency



Spurious vs Frequency

