

Model:TLPA2.5G8G-57-57-BC
**Solid State High Power Amplifier Systems
 2.5G8GHz,Gain:57dB,Psat:57 dBm**
Feature:

- Wide Band: 2.5G8GHz
- Gain: 57dB Min
- Psat Output Power:57dBm Min
- Protection:Over TEM,over voltage, over current ,over VSWR protection.
- 50 Ohm Matched Input / Output

电气特性 Electrical Specifications:

参数Parameter	代码 Symbo	Min.	Typ.	Max.	单位Units
频率范围 Frequency range	BW	2.5-8			GHz
增益 Gain	GP	57			dB
增益平坦度 Gain flatness	Δ GL		± 4		dB
饱和输出功率 Output Psat	Psat	57			dBm
杂散 Spurious @Pout=57dBm	Spur		-60	-50	dBc
谐波 Harmonics@Pout=57dBm	HAM		-15	-10	dBc
输入驻波 Input VSWR	VSWRin			2.0	:1
交流电压 AC Voltage	Vac		380		V AC
交流功耗AC Input Power	Pdiss	7500@Max			Watts
阻抗 Impedance	I/O-IMP	50			Ohms

机械特性 Mechanical Specifications:

参数Parameter	指标 Value	单位Units
输入/输出接口 Input /Output Connector	N Female/N Female	
尺寸 Size	20U*800 depth	mm
重量 Weight	100	Kg

绝对最大值 Absolute Maximum Ratings:

参数Parameter	指标 Value
输入功率 RF Input Power	10 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形尺寸 Outline Drawing:



主要功能 Key Features:



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES

参数Parameter	特点 Advantages
控制功能 Control functions	1, Power setting On/Off 2, RF setting On/Off 3, ALC automatic level control
内置保护功能 Protection functions	1, Over TEM 2, Over voltage 3, Over current protection 4, Over VSWR
通信功能 Communication functions	RS422/Ethernet
冷却系统 Cooling system	Built in Cooling system, forced air cooling

温度环境 Environmental Conditions:

参数Parameter	Min.	Typ.	Max.	单位Units
操作温度 Operating Temperature	0		+40	°C
存储温度 Non-operating Temperature	-45		+85	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	15000			feet
冲击/震动 Shock / Vibration(MIL-STD-810F)	Normal Truck Trans			

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号Revision
TLPA2.5G8G-57-57-BC	Solid State High Power Amplifier Systems 2.5-8GHz, Gain:57dB, Psat:57 dBm, 380V AC, Built in Fan Cooling	Rev.1.0