

**Model:TLPA26.5G40G-40-41-BC**
**Solid State High Power Amplifier Systems  
 26.5-40GHz, Gain:40dB, Psat:41dBm, 220V AC**
**Feature:**

- Wide Band: 26.5-40GHz
- Gain: 40dB Min
- Psat Output Power:41dBm Typ
- Protection:Over TEM,over voltage, over current ,over VSWR protection.
- 50 Ohm Matched Input / Output


**电气特性 Electrical Specifications:**

参数Parameter	代码 Symbo	Min	Typ	Max	单位Units
频率范围 Frequency range	BW	26.5-40			GHz
增益 Gain	GP	40			dB
增益平坦度 Gain flatness	$\Delta$ GL		$\pm 3$		dB
饱和输出功率 Output Psat	Psat	41	42		dBm
杂散 Spurious	Spur			-60	dBc
谐波 Harmonics	HAM			-20	dBc
输入驻波 Input VSWR	VSWRin			2	:1
交流电压 AC Voltage	Vac	220			V AC
功耗 Power Consumption	Pdiss	240			Watts
阻抗 Impedance	I/O-IMP	50			Ohms

**机械特性 Mechanical Specifications:**

参数 Parameter	指标 Value	单位Units
输入/输出接口 Input/Output Connector	2.92 Female/2.92 Female	
AC加电控制 AC Power Interface	Air switch	
尺寸 Size	19 Inch 2U	
重量 Weight	20	Kg

**绝对最大值 Absolute Maximum Ratings:**

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	260V AC
输入功率 RF Input Power	10 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V



**温度环境 Environmental Conditions:**

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-20		+60	°C
存储温度 Non-operating Temperature	-40		+65	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50000			feet
震动 Shock / Vibration(MIL-STD- 810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

**订货信息 Ordering Information:**

标准型号 Part Number	描述 Description	版本号 Revision
TLPA26.5G40G-40-41-BC	Solid State High Power Amplifier Systems 26.5-40GHz,Gain:40dB,Psat:41dBm,220V AC,Built in Fan Cooling	Rev.1.0