

## Model:TLPA800M2G-56-55-BC

## Solid State High Power Amplifier Systems 0.8-2GHz, Gain:56dB, Psat:55dBm, 220V AC

### Feature:

- Wide Band: 0.8-2GHz
- Gain: 56dB Min
- Psat Output Power:55dBm Min
- Protection:Over TEM, over voltage, over current ,over VSWR protection.
- 50 Ohm Matched Input / Output



### 电气特性 Electrical Specifications:

参数Parameter	代码 Symbo	Min	Typ	Max	单位Units
频率范围 Frequency range	BW	0.8-2			GHz
增益 Gain	GP	56	58		dB
增益平坦度 Gain flatness	$\Delta$ GL		$\pm 2$	$\pm 2.5$	dB
饱和输出功率 Output Psat	Psat		55		dBm
线性输出功率 Output P1dB	P1dB	52	53		dBm
杂散 Spurious	Spur			-60	dBc
谐波 Harmonics	HAM			-10	dBc
输入驻波 Input VSWR	VSWRin		1.5	2.0	:1
交流电压 AC Voltage	Vac	110	220		V AC
交流电流 AC Supply Current	Iac	8A@220V AC			A
阻抗 Impedance	I/O-IMP	50			Ohms

### 机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位Units
输入/输出接口 Input/Output Connector	N Female/N Female	
尺寸 Size	482.6*133.2*447	mm
重量 Weight	15	Kg

### 绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
输入功率 RF Input Power	0 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形尺寸 Outline Drawing:

Unit: mm



主要功能 Key Features:



OBSERVE PRECAUTIONS  
ELECTROSTATIC SENSITIVE  
DEVICES

参数 Parameter	特点 Advantages
控制 Control	RS422/Ethernet, LCD Screen Display
内置保护功能 Protection functions	1, Over TEM 2, Over voltage 3, Over current protection 4, Over VSWR
控制功能 Control functions	1, Power setting On/Off 2, ALC
冷却系统 Cooling system	Built in Cooling system, forced air cooling

**温度环境 Environmental Conditions:**

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	0		+50	°C
存储温度 Non-operating Temperature	-40		+85	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	15000			feet
震动 Shock / Vibration(MIL-STD- 810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

**订货信息 Ordering Information:**

标准型号 Part Number	描述 Description	版本号 Revision
TLPA800M2G-56-55-BC	Solid State High Power Amplifier Systems 0.8-2GHz,Gain:56dB,Psat:55dBm,220V AC,Built in Fan Cooling	Rev.1.0