

**Model:TLPA26.5G40G-40-40**
**Power Amplifier**  
**26.5-40GHz,Gain:40dB,Psat:40dBm**
**Feature:**

- Ultra Wide Band:26.5-40GHz
- Gain:40dB Min
- Psat Output Power:40dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

**电气特性 Electrical Specifications:**

参数Parameter	Min	Typ	Max	单位Units
频率范围 Frequency range	26.5-40			GHz
增益 Gain	40			dB
增益平坦度 Gain Flatness		±4.5		dB
饱和输出功率 Output Psat	40	41		dBm
杂散 Spurious			-50	dBc
输入驻波 Input VSWR		2	2.5	:1
直流电压 DC Voltage		+22	+24	V DC
直流电流 DC Sopply Current			7.5	A
阻抗 Impedance	50			Ohms

**机械特性 Mechanical Specifications:**


参数Parameter	指标 Value	单位Units
输入输出接口 Input /Output Connector	2.92 Female/2.92 Female	
DC加电接口 DC Power Interface	SUB-7W2	
尺寸 Size	200*100*23	mm
重量 Weight	3	Kg

**绝对最大值 Absolute Maximum Ratings:**

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+24V
输入功率 RF Input Power	10dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V


**Available 220V System  
 Benchtop Amplifier**

外形尺寸 Outline Drawing:



SUB-7W2 Define	
引脚 Pin	功能 Function
A1	+20V
A2	GND
PIN1	TTL( high for open, low for close)
PIN2	Current Monitor
PIN3	Tempert ure Monitor
PIN4/5	GND

**\*\*\*Heat Sink Required During Operation**



温度环境 Environmental Conditions:


参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	0		+40	°C
存储温度 Non-operating Temperature	-45		+65	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:


标准型号 Part Number	描述 Description	版本号 Revision
TLPA26.5G40G-40-40	Power amplifier 26.5-40GHz, Gain 40dB, Psat:40dBm, +24V DC, Without Heatsink.	Rev.1.1
TLPA26.5G40G-40-40-HS	Power amplifier 26.5-40GHz, Gain 40dB, Psat:40dBm, +24V DC, With Heatsink.	Rev.1.1

典型曲线 Typical Performance Data:


Input VSWR vs Frequency



Small Signal Gain vs Frequency




P1dB vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


Pout@Pin



Pout@Equal\_Pin



Spurious vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.