

	Electrical & Environmental Characteristics								
	Impedance	50 Ohm							
	Operating Frequency	26.5 GHz							
	Mating cycles	>2000							
	VSWR	1.15:1Max							
	Insertion Loss	0.2dB Max							
	Operating Temperature	- 55~+165℃							
	Material & Coat-Plating								
A	Inner Conductor	berylium copper, Gold Plated							
	Body	Stainless Steel, Passivated							

THIS DRAWING IS A CONTROLLED		DWN	Comban Talant Missanan Inc						
	СНК		Suzhou Talent Microwave,Inc						
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ±- 3 PLC ±- ANGLES ±1° FINISH SEE TABLE	PRODUCT SPEC	Product Model NMD2.4F3.5F NMD2.4 female to 3.5mm female adaptor						
MATEIAL SEE TABLE		N SPEC WEIGHT	SIZE A4	GAGE CODE DRAWING NO 0T8L4					A
) SEE TABLE			CUSTOMER DRAWING		SCALE 4	SCALE 4: 1	SHEET1 OF 1	RVE 1	
3	4			5					