

Model:TMAM-040060-0415-19
**Active Frequency Multiplier,
 X4,40-60GHz, 15dBm Output Power**
Feature:

- Output Frequency:40-60GHz
- Output Power :15dBm Typ
- Low power consumption

电气特性 Electrical Specifications:

参数Parameter	Min	Typ	Max	单位 Units
输出频率 Output Frequency	40		60	GHz
输出功率 Output Power		15		dBm
输入频率 Input Frequency	10		15	GHz
输入功率 Input Power	3	5	7	dBm
倍频次数 Multiply Factor		4		
输入驻波 Input VSWR		2		:1
输出驻波 Output VSWR		2		:1
供电电压 DC Voltage		8.5		V
供电电流 DC Supply Current		220		mA

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输出接口 Output Connector	WR-19/UG-383/U	
输入接口 Input Connector	SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	58*24*35	mm


绝对最大值 Absolute Maximum Ratings:

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	/
输入功率 RF Input Power	7dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V


**Available 220V System
 Benchtop Amplifier**

外形尺寸 Outline Drawing:

Unit: mm



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-10		+65	°C
存储温度 Non-operating Temperature	-25		+75	°C
相对湿度 Relative humidity		95		%
海拔 Altitude		50,000		feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号 Revision
TMAM-040060-0415-19	Active Multiplier,X4,40-60GHz, Output Power:15dBm,WR-19/UG-383/U,SMA Female	Rev.1.1