



Electrical & Environmental Characteristics

| | |
|---------------------------------|-------------|
| Impedance | 50 Ohm |
| Insulation Resistance | 5000 MΩ |
| Operating Frequency | DC~26.5GHz |
| Dielectric Withstanding Voltage | 1000V |
| VSWR | 1.15 typ |
| Insertion Loss | ≤0.30dB |
| Operating Temperature | 10mK~+125°C |

Material & Coat-Plating

| | |
|-----------------|--|
| Inner Conductor | Non-magnetic beryllium copper, Gold Plated |
| Dielectric | PTFE |
| Body&Nut | Non-magnetic beryllium copper, Gold Plated |

| | | | | | | |
|---------------------------------------|--|------------------|--|--------------------|--------------|-------|
| THIS DRAWING IS A CONTROLLED DOCUMENT | | DWN | Suzhou Talent Microwave, Inc | | | |
| | | CHK | | | | |
| Unit mm | TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1° | APVD | Product Model SMA-JJ-NM SMA Male to SMA Male adaptor with non-magnetic | | | |
| | | PRODUCT SPEC | | | | |
| | | APPLICATION SPEC | | | | |
| MATERIAL SEE TABLE | FINISH SEE TABLE | WEIGHT | SIZE A4 | GAGE CODE 0T8L4 | DRAWING NO | |
| | | CUSTOMER DRAWING | | | SHEET 1 OF 1 | RVE 1 |