

Part No: RJ4-04-01

SMA Female , Four channel

电气特性 ELECTRICAL:

	通道1 channel 1	通道2 Channel 2	通道3 Channel 3	通道4 Channel 4
工作频率 Frequency	DC-4GHz	DC-4GHz	DC-4GHz	DC-4GHz
插损 Insertion Loss	≤1dB	≤1dB	≤1dB	≤1dB
插损360度变化 Insertion Loss WOW	0.15dB	0.15dB	0.15dB	0.15dB
驻波 VSWR	≤1.4:1	≤1.5:1	≤1.5:1	≤1.5:1
驻波360度变化 VSWR WOW	0.1	0.1	0.1	0.1
功率 Power	50W@1GHz	10W@1GHz	10W@1GHz	10W@1GHz
隔离 Isolation	≥50dB			
相位一致性 Phase Balance	≤±4°			

机械特性 MECHANICAL :

转动速度 Speed:	60rpm (Max)
寿命Life time :	≥5Million cycles
启动力矩Torque :	≤ 0.8Nm
材质Material:	不锈钢Stainlessness
温度范围Temperature:	-55° C - +85° C
接口Connector:	SMA-Female
相对湿度 Humidity:	0 ~ 90%

外形尺寸Outline Drawing:

Unit: mm

